



ITALCAR INDUSTRIAL SRL | Via Bruino, 36 | 10040 Rivalta di Torino (TO) Tel. +39 011 9040225 | Fax +39 011 9032986 | info@italcar.com | www.italcar.com 48 volt with AC system 8 x 6v lead-acid batteries 205/50-10 aluminum rims front & rear lights hydraulic brakes on 4 wheels + handbrake










attiva 2L.5

places:	2
batteries:	8 x 6V, US2200 standard
motor:	AC 48V – Mahle Letrika
controller:	sevcon GEN4 – AC – 450A
transmission:	rear axle, 19 spline, ratio 12,31:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	25%
vehicle dimensions:	
overall	3600mm x 1200mm x 1800mm
cargo dimensions:	
overall	1830mm x 1100mm x 240mm
ground clearance (empty):	250mm
turning radius (min):	4 mt
wheel base	2400mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four
blakes.	wheel with hand brake
front	Disc
rear	drum
tyres:	205 / 50 – 10 with aluminium rims
recommended pressure:	1,7 bar (25psi)
battery charger:	included with the vehicle - 48v, 220/230V
100	Includes:
basic configuration:	reverse buzzer; digital speedometer, front and rear
	lights, horn, direction indicators, rear-view mirrors, one
	piece plexiglass

All above specification were correct at the time of the printing and are considerated indicatives and not binding. ITALCAR INDUSTRIAL S.r.I. maintains the right to bring any changes without notice





clicca mi piace - like us on



seguici su - follow us on



