




attiva 4L.5



48 VOLT WITH AC SYSTEM
8 X 6V LEAD-ACID BATTERIES
205/50-10 ALUMINUM RIMS
FRONT & REAR LIGHTS
HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE



ITALCAR an Italian Brand



attiva 4L.5

places:	4
batteries:	8 x 6V, US2200 standard
motor:	AC 48V – Mahle Letrika
controller:	sevcon GEN4 – AC – 450A
transmission:	rear axle, 19 spline, ratio 12,31:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	25%
vehicle dimensions:	
overall	3800mm x 1200mm x 1800mm
cargo dimensions:	
overall	900mm x 1100mm x 240mm
ground clearance (empty):	210mm
turning radius:	4 mt
wheel base	2400mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel with hand brake
front	Disc
rear	drum
tyres:	205 / 50 – 10 with aluminium rims
recommended pressure:	1,7 bar (25psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: reverse buzzer; digital speedometer, front and rear lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

All above specification were correct at the time of the printing and are considered indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice

clicca mi piace - like us on



segui su - follow us on

