



attiva xtr 2.5




- 48 VOLT WITH AC SYSTEM
- 8 X 6V LEAD-ACID BATTERIES
- 22X11-12 ALUMINUM RIMS
- FRONT & REAR LIGHTS
- MECHANICAL BRAKES ON REAR WHEELS



attiva xtr 2.5

places:	2
batteries:	8 x 6V, US2200 standard
motor:	AC 48V – Mahle Letrika
controller:	sevcon GEN4 – AC – 450A
transmission:	rear axle, 19 spline, ratio 12,31:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	20%
dimensions:	
overall	3000mm x 1400mm x 2150mm
ground clearance (empty):	350mm
turning radius (min):	3,5 mt
wheel base	1710mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	
rear	mechanical brake on rear wheels drum
tyres:	22 x 11 – 12 with aluminium rims
recommended pressure:	2 bar (29psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: reverse buzzer; digital speedometer, front and rear lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

All above specification were correct at the time of the printing and are considered indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice



clicca mi piace - like us on



segui su - follow us on

