



nev C2C.5



48 VOLT WITH AC SYSTEM

AGM OR LI BATTERIES


145/70 R12 ALUMINUM RIMS

LED LIGHTS WITH DRL
FUNCTION

HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE



nev C2C.5



places:	2
batteries:	AGM pack or LI pack
motor:	AC - 48v
controller:	AC – 450A
transmission:	rear axle, ratio 12,49:1
steering:	self compensating single reduction rack and pignon
performances:	
max speed:	45 km/h (L6e) - 55 km/h (L7e)
range:	(agm) 80 km – (li) 120km
max hill climbing ability:	20%
dimensions:	
overall (LxWxH)	2700mm x 1280mm x 1660mm
dimensions:	
cargo (LxWxH)	1000mm x 1200mm x 300mm
ground clearance (empty):	120mm
turning radius:	4,5 mt
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel with hand brake
front	disc
rear	drum
tyres:	145 / 70 – 12 with aluminum rims
reccomended pressure:	2,5 bar (25kPa)
battery charger:	included
basic configuration:	open-type T doors, 3 points safety belts, glass windshield, front & rear lights and turning lights, reverse buzzer, folding rearview mirrors, rear trunk with key lock, 12v socket, wiper and washing system, HI-FI (radio+speakers), heating system
optional	whole glass doors

clicca mi piace - like us on



segui su - follow us on



All above specification were correct at the time of the printing and are considered indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice